

## Granite Handling Instructions

- Inspect Granite carefully upon arrival for damage in transit.
- If damaged, DO NOT accept delivery of merchandise. Describe the damage on the truck bill of lading. Notify Lowe's your order arrived damaged and schedule shipment of a replacement as soon as possible.
- Granite is fragile and will break easily if not handled properly.
- Granite vanity tops are heavy and should always be carried in vertical upright position by two (2) persons holding each end.
- DO NOT lift granite vanity top from the bowl cutout area. This is the weakest part of the stone.
- DO NOT lay granite flat or transport in a horizontal position.
- The following items are included in granite vanity top packaging:
  - 2 x side splashes
  - 1 x backsplash
  - 1 x granite vanity top
  - 1 or 2 under mount bowls
  - 1 x packet of mounting clips and winged bolts or nuts
  - Installation Instructions with Warranty
- Upon completing the inspection, granite vanity top should always be stored in vertical upright position on the original pallet provided by the manufacturer until ready for installation.
- If customer does not have suitable transportation to transport granite vanity top on the original pallet in vertical upright position, we recommend customer to contract Lowe's to deliver to customer.
- Granite vanity tops are sealed at the factory with a protective sealer and should be re-sealed by the customer prior to use and as often as required thereafter. Granite sealer may be purchased from Jackson Stoneworks or from Lowe's Home Improvement Stores.